# High Definition Digital Camera - HD-DC



### **High Definition Digital Camera**

Use this High Definition Digital Camera (HD-DC) to visually inspect your enterprise assets and resources via your browser from anywhere in the world. The AKCess Pro HDDC provides optimum features for deployment with the AKCess Pro securityProbe 5ES Video series.

The AKCess Pro HD-DC is ideal for use with the securityProbe, capable of accepting 2 cameras and the AKCess Server application, that can connect many HD-DC's for recording and playback of video footage. Still images

are in Universal JPG digital format, allowing easy use of third party host tools to store and analyze your pictures.

#### Note:

A power supply is not required with this item.

### **Rich Notification Suite**

Real-time and archived video and pictures can be included in your alert notifications according to your preferred hierarchy of redundant alert notifications. Choose any notification combination and sequence from our Rich Notification Suite, to escalate unresolved alerts.

- SMS
- Email
- MMS
- Telephone call
- Fax
- SNMP
- Relay switch automates corrective action.

## **USB Digital Camera: Technical Specifications**

	<del>-</del>
Image Sensor	IR Range of 20 Meters 1/3" CMOS Auto White Balance 640 Pixels per Line with 625 per frame (interlaced)
Picture Elements	640 (H) x 480 (V) 352 (H) x 288 (V)
Illumination	0.5 Lux (Color), 0 Lux (Black & White)
S/N Ratio	< 48dB
Power	Power by securityProbe or Door Control Unit
Codec	MJPEG
Lens Type	Fixed
Focal Length	3.6mm