



3G-9350

19" Rackmount 3G SDI Monitor



DISPLAY

LCD Type	5" TFT Active Matrix Panel
Display Area	108 (H) mm x 64.8 (V) mm
Pixel Pitch	0.135 x 0.135 mm
Brightness	300 cd/m ²
Contrast Ratio	600 : 1
Response Time	25 msec
Viewing Angle	170° (H) / 170° (V)
Display Colors	16.7M Colors
Resolution	800 x 480 pixels (16:9)

INTERFACE

3G/HD/SD-SDI (IN)	BNC X 1
SDI Active Through (OUT)	BNC X 1
YPbPr (IN)	BNC X 3
HDMI (IN)	HDMI X 1
CVBS (IN)	BNC X 1
S-Video (IN)	Mini-DIN X 1
VGA (IN)	D-SUB(15 pin) X 1
TALLY (IN)	D-SUB(9 pin) X 1

FORMATS

3G	1080P (50 / 59.94 / 60)
HD	1080P (24 / 25 / 30)
	1080i (50/ 59.94 / 60)
	1035i (50/ 59.94 / 60)
	720P (50 / 59.94 / 60)
SD	576i (50)
	480i (59.94)
YPbPr	720P/ 1080i /1080P
CVBS, S-Video	NTSC (525/59.94), PAL (625/ 50)
VGA	VGA, SVGA, XGA
HDMI	480i / 480P / 576i /576P/ 1080i /1080P

OTHER

Power Adapter	AC 100 ~ 240V , 50/60Hz
Power Consumption	38 Watts
Temperature	Operation : 0°C ~ +50°C Storage : -20°C ~ +60°C
Dimension	483 x 132 x 175 mm (3U)
Gross Weight	6 Kg + 500 g
Regular Approvals	FCC, CE, RoHS

DIMENSION (unit:mm)

