



# 3G-9443

## 19" Rackmount 3G SDI Monitor



DISPLAY	
LCD Type	4.3"TFT Active Matrix Panel
Display Area	93 (H) mm x 55.8 (V) mm
Pixel Pitch	0.116 x0.116 mm
Brightness	200 cd/m2
Contrast Ratio	400 : 1
Response Time	20 msec
Viewing Angle	160° (H) / 130° (V)
Display Colors	16.7M Colors
Resolution	800 x 480 pixels (16:9)
INTERFACE	
3G/HD/SD-SDI (IN)	BNC X 1
SDI Active Through (OUT)	BNC X 1
YPbPr (IN)	BNC X 3
HDMI (IN)	HDMI X 1
CVBS (IN)	BNC X 1
S-Video (IN)	Mini-DIN X 1
VGA (IN)	D-SUB(15 pin) X 1
TALLY (IN)	D-SUB(9 pin) X 1

FORMATS	
3G	1080P (50 / 59.94 / 60 )
HD	1080P (24 / 25 / 30 )
	1080i (50/ 59.94 / 60 )
	1035i (50/ 59.94 / 60 )
	720P (50 / 59.94 / 60 )
SD	576i (50 )
	480i (59.94 )
YPbPr	720P/ 1080i /1080P
CVBS, S-Video	NTSC (525/59.94), PAL ( 625/ 50)
VGA	VGA, SVGA, XGA
HDMI	480i / 480P / 576i /576P/ 1080i /1080P
OTHER	
Power Adapter	AC 100 ~ 240V , 50/60Hz
Power Consumption	46 Watts
Temperature	Operation : 0°C ~ +50°C Storage : -20°C ~ +60°C
Dimension	483 x 132 x 175 mm ( 3U )
Gross Weight	7 Kg + 500 g
Regular Approvals	FCC,CE,RoHS

### DIMENSION (unit:mm)

