



# HD-6150

## Stand alone HD SDI Monitor

- HD-SDI
- HDMI
- CVBS
- YC
- YPbPr
- VGA
- L/R BALANCE
- TALLY
- MARKER
- HV DELAY
- BLUE ONLY
- MONO ONLY
- SCAN UNDER/OVER

DISPLAY	
LCD Type	15" TFT Active Matrix Panel
Display Area	304 (H) mm x 228 (V) mm
Dot Pitch	0.297 mm
Brightness	250 cd/m <sup>2</sup>
Contrast Ratio	600 : 1
Viewing Angle	160°(H) / 160° (V)
Display Colors	16.7 Million Colors
Resolution	1024 x 768 pixels (4:3)
INTERFACE	
HD/SD SDI Auto-switch (IN)	BNC X 1
SDI Active Through (OUT)	BNC X 1
YPbPr (IN)	BNC X 3
HDMI (IN)	HDMI X 1
CVBS(IN)	RCA X 2
S-Video (IN)	Mini-DIN X 1
VGA (IN)	D-SUB(15 pin) X 1
AUDIO L / R (IN)	RCA X 2
TALLY (IN)	D-SUB(9 pin) X 1
STERTO (IN)	Phone Jack X 1

AUDIO	
speaker	2 X 2.5W
FORMATS	
SDI	1080P (23.98 / 24 / 25 / 29.97 / 30)
	1080PsF (23.98 / 24)
	1080i (50 / 59.94 / 60)
	1035i (59.94 / 60)
	720P (50 / 59.94 / 60)
	480i (59.94 / 60)
576i (50)	
HDMI	480i / 480P / 576i / 576P / 720P / 1080i / 1080P
YPbPr	720P / 1080i / 1080P
CVBS, S-Video	NTSC (525/59.94i), PAL ( 625/ 50i)
VGA	VGA, SVGA, XGA, SXGA
OTHER	
Power Adapter	AC 100 ~ 240V , 50/60Hz
Power Consumption	36 Watts
Temperature	Operation : 0°C ~ +50°C Storage : -20°C ~ +60°C
Dimension	464 x 319.5 x 59.2 mm
Gross Weight	6.5 Kg + 500 g
Regular Approvals	FCC, CE, RoHS

## DIMENSION (unit:mm)

