



HD-6173

Stand alone HD SDI Monitor

HD-SDI	HDMI	CVBS	YC
YPbPr	VGA	L/R BALANCE	TALLY
MARKER	H/V DELAY	BLUE ONLY	MONO ONLY
SCAN UNDER/OVER			

DISPLAY	
LCD Type	17.3" TFT Active Matrix Panel
Display Area	381.8 (H) mm x 214.8 (V) mm
Dot Pitch	0.198 mm
Brightness	400 cd/m ²
Contrast Ratio	600 : 1
Viewing Angle	160° (H) / 140° (V)
Display Colors	16.7 Million Colors
Resolution	1920 x 1080 pixels (16:10)
INTERFACE	
HD/SD SDI Auto-switch (IN)	BNC X 1
SDI Active Through (OUT)	BNC X 1
YPbPr (IN)	BNC X 3
HDMI (IN)	HDMI X 1
CVBS(IN)	RCA X 2
S-Video (IN)	Mini-DIN X 1
VGA (IN)	D-SUB(15 pin) X 1
AUDIO L / R (IN)	RCA X 2
TALLY (IN)	D-SUB(9 pin) X 1
STERTO (IN)	Phone Jack X 1

AUDIO	
speaker	2 X 2.5W
FORMATS	
SDI	1080P (23.98 / 24 / 25 / 29.97 / 30)
	1080PsF (23.98 / 24)
	1080i (50 / 59.94 / 60)
	1035i (59.94 / 60)
	720P (50 / 59.94 / 60)
	480i (59.94 / 60)
576i (50)	
HDMI	480i / 480P / 576i / 576P / 720P / 1080i / 1080P
YPbPr	720P / 1080i / 1080P
CVBS, S-Video	NTSC (525/59.94i), PAL (625/ 50i)
VGA	VGA, SVGA, XGA, SXGA
OTHER	
Power Adapter	AC 100 ~ 240V , 50/60Hz
Power Consumption	36 Watts
Temperature	Operation : 0°C ~ +50°C Storage : -20°C ~ +60°C
Dimension	464 x 317 x 59.2 mm
Gross Weight	8 Kg + 500 g
Regular Approvals	FCC, CE, RoHS

DIMENSION (unit:mm)

