



# HD-9150

## Stand alone HD SDI Monitor



DISPLAY	
LCD Type	15"TFT Active Matrix Panel
Display Area	304 (H) mm x 228 (V) mm
Dot Pitch	0.297 mm
Brightness	250 cd/m2
Contrast Ratio	600 : 1
Viewing Angle	160°(H) / 160° (V)
Display Colors	16.7 Million Colors
Resolution	1024 x 768 pixels (4:3)
INTERFACE	
HD/SD SDI Auto-switch (IN)	BNC X 1
SDI Active Through (OUT)	BNC X 1
YPbPr (IN)	BNC X 3
HDMI (IN)	HDMI X 1
CVBS(IN)	RCA X 2
S-Video (IN)	Mini-DIN X 1
VGA (IN)	D-SUB(15 pin) X 1
AUDIO L / R (IN)	RCA X 2
TALLY (IN)	D-SUB(9 pin) X 1
STERTO (IN)	Phone Jack X 1

AUDIO	
Speaker	2 X 2.5W
FORMATS	
SDI	1080P (23.98 / 24 / 25 / 29.97 / 30)
	1080PsF (23.98 / 24)
	1080i (50 / 59.94 / 60)
	1035i (59.94 / 60)
	720P (50 / 59.94 / 60)
	480i (59.94 / 60)
576i (50)	
HDMI	480i / 480P / 576i / 576P / 720P / 1080i / 1080P
YPbPr	720P/ 1080i / 1080P
CVBS, S-Video	NTSC (525/59.94), PAL (625/ 50)
VGA	VGA, SVGA, XGA, SXGA
OTHER	
Power Adapter	AC 100 ~ 240V , 50/60Hz
Power Consumption	36 Watts
Temperature	Operation : 0°C ~ +50°C Storage : -20°C ~ +60°C
Dimension	483.5 x 310.3 x 87.65 mm ( 7U )
Gross Weight	6.5 Kg + 500 g
Regular Approvals	FCC,CE,RoHS

## DIMENSION (unit:mm)

