

# IPM1016-WU35L0

## Specification

IP65 front Panel Mount, 10.1" LCD monitor, 1920 x 1200, LED 350 nits, VGA input



### Features

- IP65 front side sealed for water-dust proof
- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- VGA connector with optional AV,SV,AV-Looping
- Complete custom design/solution for OEM customers

|                     |  |   |   |
|---------------------|--|---|---|
| Panel               | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating          |   |
|                     | Aspect Ratio / Size  | Wide / 10.1" viewable diagonal area                         |   |
|                     | Active Area / Pixel Pitch  | 216.81(H) x 135.5(V) mm / 0.113(H) x 0.113(V) mm            |   |
|                     | Native Resolution / Colors   | 1920(H) x 1200(V) / 16.7M                                   |   |
|                     | Brightness / Contrast  | 350 cd/m <sup>2</sup> (typ) / 600 : 1                       |   |
|                     | Response Time  | ≤ 25 ms   |   |
|                     | Viewing Angle (typical)  | H.160° (- 80° ~ + 80°) , V. 160°(- 80° ~ + 80°)             |   |
|                     | Light Source   | LED backlight, Long life, 35,000 hrs (typ)                  |   |
| Input Sources       | PC System  | Signal  | Analog RGB (0.7/1.0 V <sub>pp</sub> , 75 ohms)          |
|                     |  | Sync  | Separate Sync, Composite Sync, Sync On Green            |
|                     |  | Frequency   | F <sub>h</sub> : 30 - 82Khz , F <sub>v</sub> : 50 -75Hz |
|                     | Audio System   | 2W speaker x 2  |   |
| Input Terminals     | 1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug |   |   |
| Convenient Features | Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)               |   |   |
|                     | OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)        |   |   |
| Power               | 12V DC in  |   |   |
| Power Consumption   | Operation / Power Saving   | 8.75 watt , < 1 watt (Support DPMS)                         |   |
| Operating Condition | Temperature / Humidity   | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |   |
| Storage Condition   | Temperature / Humidity   | - 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation) |   |
| Certification       | FCC , CE   |   |   |
| Dimensions          | Physical   | Please refer to Drawing                                     |   |
|                     | Carton   | W x H x D = TBD   |   |
| Weight              | N.W. / G.W.  | 3.5 Kgs / 4.5 Kgs   |   |
| Container Loaded    | 20ft / 40ft / 40ft HQ  | TBD (Sets , By pallet)                                      |   |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | Infrared touch   | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Protected glass  |                      | Sunlight Readable        | Light Sensor                 |
|         |                  |                      |                          | Auto-Dimming                 |