

# INR-401

## 256-Channel RAID Rackmount Standalone NVR with Redundant Power Supply



- 12-bay Rackmount Standalone NVR
- Rack Space: 2U
- Hardware RAID 0, 1, 5, 6, 10, 50, 60
- Maximum Number of Video Devices: 256
- Free License: 64 (64 channels for ACTi and 1 channel for third-party video device)
- Event trigger, response and notification
- Workstation, Web Client, Mobile Client
- Video export formats: RAW, AVI, EXE
- Location-based management with e-Map
- Non-ACTi camera support via licensed Camera Device Pack
- Redundant Power Supply
- Intel Core i7-6700, 16GB

### ► Specifications

#### Device

Product Type	Standalone NVR
Maximum Resolution	Support all ACTi cameras in all resolutions
Maximum Number of Video Devices	256
Maximum Number of POS devices	256 (requires additional license)
Maximum Number of Access Control and Network I/O devices	256 (requires additional license)
Maximum Number of Clients	Local: 1, Remote: 5

#### Hardware

CPU	Intel Core i7-6700
RAM	16GB, DDR4, 2400MT/s

**License**

License required	Yes
Free License	64 (64 channels for ACTi and 1 channel for third-party video device)

**Live View**

Display Layout Mode	1, 3, 4, 5, 6, 8, 9, 10, 12, 16 Remote:1, 3, 4, 5, 6, 8, 9, 10, 12, 16, 18, 24, 25, 35, 36, 48, 49, 64, Custom
Fisheye Dewarping	Yes
Local Live View performance	Please check "Standalone NVR Performance Validator" ( <a href="http://www.acti.com/SANVRPerformance">http://www.acti.com/SANVRPerformance</a> )
Digital Zoom	Yes
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client or when the allocated disk space is full
Instant Playback	Instant Playback in live view window
Embedded websites in Live View	Display and connect to pre-configured embedded website

**Map**

e-Map	Yes
Google Map	Yes
Layout	Area maps with camera icons, small live view windows, hyperlinked
Setup	e-Map image upload, Google maps settings and preset management, camera positioning, vision angle and pointed direction of camera, view positioning, source positioning, extended devices for Point-of-sale (POS), Access Control, Network I/O, Car Park
PTZ Mode	Mouse PTZ mode to control e-Map video streams

**PTZ**

PTZ Control	PTZ Control, Speed Control, 32 preset points
Joystick	USB based joystick supported

**Video**

Compression	H.265, H.264, MPEG-4, MPEG
Built-in Analytics	Visual Tracking

**Audio**

Audio Type	2-way, Mic-in, Line-in, Line-out
------------	----------------------------------

**Network**

Network Protocol & Service	IPv4/v6, TCP, UDP, DHCP Client, HTTP, DNS, NTP, RTP, SMTP, FTP, ICMP, ARP, UPnP, LDAP (client), iSCSI
Ethernet Port	2 x Ethernet (1000 Base-T), RJ-45 connector

**Recording**

Scheduled Recording	Yes
Event Recording	Yes
Manual Recording	Yes

Event Speed-up Recording	Yes
Dual Stream Management	Yes
Maximum Recording Throughput	300 Mbps

### Search & Playback

Playback Control	Continuous forward and backward playback with speeds 1x/2x/4x/8x/16x or frame-by-frame, pause, stop
Synchronized Playback	9 channels (Local), 64 channels (Remote)
Recording Search	Search video recordings by time, events, channels, bookmarks, notifications and listed as clickable time-based thumbnails for full-size view and snapshot download
Smart Search	Smart search of recorded video by Motion Detection and Tamper
Video Export	RAW, AVI, EXE
Snapshot Export	BMP, JPEG, PNG

### Event

Video Push	Support Video Push from ACTi Mobile Client devices
Event Trigger	[NVR]: Disk full, Disk not found, Disk is available, Schedule service start and stop, Video Push start and stop, CPU limit exceeded. [Video Device]: Video motion detection, Passive IR sensor, External device through digital input, Sound detection, Intelligent event detection, RFID detection, Video Push start and stop, Video loss, Video Recovery, Network loss and recovery [Extended Device]: Point-of-sale (POS) status, Network I/O status, Access Control status, Car park status
Event Response	Pop-up window with live video and event confirmation activation, Switch to hotspot window, Switch to customize view, Command a PTZ device to go to a preset point, Play alert sound, Activate external device through digital output, Execute system command to activate other programs, Upload snapshot to FTP server, E-mail notification with snapshots, Push notification

### Redundancy Server

Redundancy Service	Yes, N-to-N, N+1 (With limited functions when NVR 3 server acts as Redundancy server)
--------------------	---

### System

Permission control	Unlimited number of users, Active Directory, Customizable permissions for user groups, Account lockout, Automatic logout after idle, Playback password protected, Password validity period
Client PC Operating System	Windows 7 SP1, Windows 8.1, Windows 10, Windows Server 2008 R2 SP1, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Server Operating System	Windows 10 IoT
Mobile Client Program	Mobile device application (ACTi Mobile Client) supports Live View, PTZ Control, Video Push, Event/time based search and playback, iPad, Android device
USB	5-Port USB 3.0
Language	Multi-Language

### Integration

Unified Solution	Fully compatible with ACTi cameras, encoders, central management system, TV wall and intelligent video surveillance software
------------------	--

GPS Position	Manual setting
ONVIF Compliant	Yes, Profile S
Web Browser	IE 11 (Please verify that your computer meets the minimum system requirements for Internet Explorer from Microsoft website.)
Third-party Integration	Point of Sale (POS), Access Control, Network I/O, Parking Management Station (PMS), (Various optional integrations requiring additional license)

## Storage

Supported Storage Technology	SAN, NAS
System Drive	SSD, 256GB
Hot Swappable Drive	Yes
Storage Bay	SATA, Max. 12 Disk(s) (without storage disks)
HDD Size	3.5"
Maximum Recording Capacity	14TB x12
RAID Level	Hardware RAID 0, 1, 5, 6, 10, 50, 60
Supported Storage	Video Recording: SATA disk, Export: USB

## Interface

Serial Port	1 x RS-485/RS-422
Audio Interface	1/1, 3.5mm Phone Jack
External Storage Interface	iSCSI, USB
Local Access	USB joystick, keyboard & mouse
Local Display Interface	HDMI x 2, VGA x 1, DVI x 1 (maximum two ports concurrent use)

## General

Power Source	AC 100-240V
Redundant Power Supply	Yes, 550W x 2
Weight	16000g (35.274lb)
Dimensions	(W x H x D): 482.6 mm x 87mm x 625mm (19" x 3.5" x 24.61") Rack Space: 2U
Bundled Accessories	Power cord
Mount Type	Rack mounts
Fan	Yes
Operating Temperature	0°C ~ 60°C (32°F ~ 140°F)
Operating Humidity	0% - 95% RH
Remote Access	Workstation, Web Client, Mobile Client
Approvals	BSMI
Color	Silver
Warranty	3 Year(s). For extended warranty offering, see <a href="http://www.acti.com/support/warranty">http://www.acti.com/support/warranty</a>

## ► Ordering Information

LEXD3000	<p>The license is for network I/O or access control extended device to work on NVR 3 Corporate. The number of add-on devices supported: 1-100. Price listed is for single device add-on license. NVR 3 Corporate: The software NVR with support up to 100 cameras or video encoders; Smart Search; Export video; Event management; e-Map; free license for 1-channel ACTi and 1-channel third-party video devices included; Support for integration with POS, access control and extended device by additional software license.</p>
LNVR3003	<p>The license is for channel (ACTi video devices) to work on NVR 3 Corporate, GNR series, INR series, MNR-310. The number of add-on channels supported: 1-199 (NVR 3 Corporate), 1-136 (INR-4xx), 1-64 (GNR-410), 1-32 (GNR-3xx, GNR-3000, INR-340), 1-16 (MNR-310). Price listed is for single channel add-on license. NVR 3 Corporate: The software NVR with support up to 200 cameras or video encoders; Smart Search; Export video; Event management; e-Map; free license for 1-channel ACTi and 1-channel third-party video devices included; Support for integration with POS, access control and extended device by additional software license.</p>
LPOS3000	<p>The license is for POS device to work on NVR 3 Corporate. The number of add-on devices supported: 1-100. Price listed is for single device add-on license. NVR 3 Corporate: The software NVR with support up to 100 cameras or video encoders; Smart Search; Export video; Event management; e-Map; free license for 1-channel ACTi and 1-channel third-party video devices included; Support for integration with POS, access control and extended device by additional software license.</p>