Step 4: Access the Device

On Network with DHCP Server / Router (Automatic IP)

- 1. Connect the device and the PC within the same network segment. Once connected, an IP address will be assigned to the Camera.
- 2. Find the Camera via Windows Explorer or IP Utility.

By Windows Explorer

- a. Go to Start > My Computer > Network.
- b. Double-click on the device name.

Organize • Search A	ctive Directory Network and Sharing Ce	rter Add a printer 🤬 💥 💌 🔳	
 ★ Favoritas ■ Desktop 	B19-A-XX-14D-00008	BIBMA-XX-140-0018	
Downloads	BI8-A-XX-14D-00018	682A-XX-13C-00016	
) 🔛 Libraries	F72A-X6-13D-00166	K 👔 62-4-XX-13C-40372	
> : S Computer	ESLA-XX-121-00073	545A-XX-138-00056	
r w retwork	~		

By IP Utility

- Download IP Utility from our website (<u>www.acti.com</u>).
- b. Run IP Utility to start searching for network devices.
- c. Click the IP address of the Camera.

O	Rebest	Device Settings	Change Selwork Address	s Prevare Uppade	Config Backup	Config Restore Re	sel SaveSitebool
	Account	adrin Passwor					
	PASSING	Senal No.	MAC Address	Fillipping	Model	Wuttcest P	
0	172.16.26.126	E91-A-XX-538-00154	00.07.70.64.00.09	A10-580-VE 05 15-AC	Megapinal P Dome	221.5.6.1	
	172 16 26 35	E918-A-XX-14D-00018	00.0P.7C.00.5P.17	A10-500-VE 07.10-AC	Megapikel IP Dome	228.5.6.1	
	172.16.26.190	E918-A-XX-14D-00019	000F7C005F00	A10-680-VE.07.10-AC	Megapical IP Come	228.5.8.1	
	172.16.26.21	C9108A-XX-140-80018	0007700057.90	A10-580-VE 07.10-AC	Megapixal P Come	226.5.6.1	
	172 18 26 34	F018-8-30C-140-80088	00-0P TC 00-5P 00	A10.400.VE07.10.AC	Hentspherie Camera	228.6.6.1	
		E9198A-301-142-80088	000770006871	A10-585-VE 87.15-AC	Henispheric Camera	228.5.6.1	
0	123.10.50.55	PARTY IN COLUMN PARTY.	10.00 TO 10.00 AL	A 100 A 100 A 100 A 100 A 100	Number of Concession	200.0.0.1	
	172 16 25 40	E8216A-301-140-80018	00-07 70:00-68.99		Henispheric Camera	228.5.6.1	
0	172.16.26.33	300 145-55515	00.07 TC 00.68 AD	A10-585-VE-87.15-AC	Megapixal P Done	228.5.8.1	
	172.16.25.39	1-00-140-80018	000770004801	A10-580-VE 07.10-AC	Megapixal P Dome	228.5.6.1	
	172.16.28.43	223-006 140-00018	000770004805	A10-500-VE07.10-AC	Henispheric Camera	226.5.6.1	
	172.18.26.135	E923-A-000 142-00019	00.07.70.00.68.06	A10-585-VE-07.10-AC	Henispheric Camera	228.5.6.1	
	172.16.26.30	E9236A-301-142-80018	0007700048.09	A10-588-VE-87.19-AG	Henispheric Camera	228.5.6.1	
	172.16.26.122	EH-A-01-13-00054	00.0f 30.09 AE 80	A10-500-VE 07.07-AC	Megapixel P Dome	228.5.6.1	
	192.100.0.151	E95-A-XX-130-00016	000F7C0827.0F	A10-580-VE 05.21-AC	Megapost P Dome	226.5.6.1	
	172.16.25.141	E97-A-306-536-00147	00:07:70:00:00:5A	A10-588-VE 85.20-AC	Megapixal P Dome	228.5.6.1	
	172 16 26 36	ESE-A.XX.140.00018	00-0F-7C-00-64-68	A10.689.VE 07.10.AC	Henissheris Camera	228.6.6.1	

3. The **Web Configurator** appears with the IP address of the Camera on the URL bar. Login to access the Camera.

Note: For full functionality, it is recommended to use Microsoft Internet Explorer[®]. When using non-IE browsers, free 3rd party software plug-ins may be required. Refer to the device Firmware Manual for more information.

On Network without DHCP Server (Default IP)

1. If necessary, configure the IP settings of your PC to match with the network segment of the Camera.



How to configure the PC IP address?

Click Start > Control Panel > Network and Sharing Center > Change adapter settings. Then follow the steps below:

1	3 Local Area Connection Networking Shareg	a Properties
Control Panel Home Menge avinetis networks Change advects instruction Change advects instruction Change advects during Entrol HermoRoung Internet Options Windows Firewall	Corect and the constraints of th	BOTTOC E Grand Harmon Control (100 Med Regram) Monte Statement (100 Med Regr

2. Open a web browser and type **192.168.0.100** on the URL address bar. The **Web Configurator** appears. Login to access the Camera.

Note: For full functionality, it is recommended to use Microsoft Internet Explorer[®]. When using non-IE browsers, free 3^{cd} party software plug-ins may be required. Refer to the device Firmware Manual for more information.



Step 5: Log-in

- 1. For first time login, set up the root account **Name** and **Password**.
- 2. Click Apply.



- 3. On the Login page, type the newly setup **Account** name and **Password**.
- 4. Click Login.

The **Live View** screen appears.

5. Click to access the **Setup** menu to modify the Camera settings.





For more detailed instructions, please refer to the "Firmware Manual" downloadable from the website (<u>www.acti.com</u>).

ACTi Connecting Vision and its logo are registered trademarks of ACTi Corporation. Microsoft[®] and Windows[®] are registered trademarks of Microsoft Corporation. All other products or company names mentioned in this document are trademarks or registered trademarks of their respective owners.

Copyright © 2014, ACTi Corporation All Rights Reserved

Quick Installation Guide

This guide contains the basic information you need to quickly setup the Camera. For detailed information on installations or operations, please refer to the Hardware Manual and Firmware Manual on ACTi website (<u>www.acti.com</u>).

Step 1: Unpack the Device

Check the camera package and make sure all items are present. The complete package list is shown on the camera Hardware Manual.

Step 2: Mount the Device

Mounting varies per camera model. Check the most suitable mounting method from the Hardware Manual or from our Mounting Accessory Selector Tool (<u>www.acti.com/mountingselector</u>).

Step 3: Connect the Device

Basic Connection Example

