



Benefits

- ▶ 6U 17" LCD display panel
- ▶ 1920 x 1080 native resolution / 16.7M colors (8-bit)
- ▶ 1000 cd/m² brightness
- ▶ HDMI 1.4 + VGA video input (speakers excluded)
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- Dual stereo speakers for HDMI (**HS4.4**)
- DVI-D + Audio input & output + Speakers (**DV4.4**)
- DP 1.0 + HDMI 2.0 + Audio input & output + Speakers (**DP**)
- Composite + Audio IN + Speakers (**BNC**)
- 3G / HD / SD-SDI Broadcast-grade input + Speakers (**SDI**)
- Multi display OSD controller (**MCS**)
- MIL-type or lockable connector
- DC power : 12V / 24V / 48V / 125V / 250V
- Touchscreen : Projected Capacitive 10-pt / Resistive 1-pt

Product Specifications

| Video | |
|-------------|----------------|
| Video input | HDMI 1.4 + VGA |

| Video Option | | |
|--------------|-------------------|---------------------|
| Digital | HDMI | HDMI 2.0 / HDCP 2.2 |
| | DVI-D | DVI-D single link |
| Analog | Composite (BNC) | NTSC & PAL |

| LCD Panel | |
|---------------------------|--------------------------|
| Panel size (diagonal) | 17.3" |
| Native resolution | 1920 x 1080 |
| Brightness (cd/m²) | 1000 |
| Contrast ratio (typ.) | 600 : 1 |
| Colors | 16.7 M, 8-bit |
| Viewing angle (L/R/U/D) | 80/80/60/80 |
| Response time (ms) | 5.5 |
| Dot pitch (mm) | 0.1989 |
| Display area (mm) | 381.888H x 214.812V |
| Surface treatment | Anti-glare, Hard-coating |
| Surface hardness | 3H |
| Backlight type | LED |
| MTBF (hrs) | 50,000 |

| Audio Option | | |
|--------------|--------------------------|-------------------|
| Input | Connector | 3.5mm stereo jack |
| | Impedance / Power level | 30kΩ / 750mV |
| Output | Connector | 3.5mm stereo jack |
| | Resistance / Power level | 30kΩ / 2.8V |
| Speaker | Dual stereo | 2W x 2 |

| Power | | |
|-------------|---------------------------------------|----------|
| Input | Auto-sensing 100 to 240VAC, 50 / 60Hz | |
| Consumption | Screen on | Max. 39W |
| | Power saving mode | Max. 2W |
| | Power button off | Max. 1W |

| Environment | |
|------------------------|------------------------------------|
| Operating temp. | 0 to 55°C degree |
| Storage temp. | -20 to 60°C degree |
| Operating humidity | 10~90%, non-condensing |
| Storage humidity | 5 ~90%, non-condensing |
| Operating altitude | 16,000 ft |
| Non-operating altitude | 40,000 ft |
| Shock | 10G acceleration (11ms duration) |
| Vibration | 10~300Hz 0.5G RMS random vibration |

| Compliance | |
|-------------|----------------------|
| EMC | FCC & CE |
| Safety | CE / LVD & UKCA |
| Environment | REACH & RoHS3 / WEEE |

| Physical | | |
|--------------------------|---------|--|
| Dimensions (W x D x H) | Product | 480 x 48 x 266 mm 18.9 x 1.9 x 10.5 inch |
| | Packing | 529 x 124 x 451 mm 20.8 x 4.9 x 17.8 inch |
| Weight | Net | 4.5 kg / 9.8 lb |
| | Gross | 6 kg / 13.2 lb |

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Diagrams (mm)

