



### Benefits

- ▶ 1U 17" / 19" LCD display drawer
- ▶ 1152 x 900 SUN Micro resolution / 16.7M colors
- ▶ HDMI 1.4 + VGA video input (speakers excluded)
- ▶ Short depth design of 500mm
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front panel and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

### Options

- DC power : 12V / 24V / 48V / 125V / 250V

## Product Specifications

Video	
Video input	HDMI 1.4 + VGA

Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

LCD Panel	SP-117	SP-119
Panel size (diagonal)	17"	19"
Resolution	Direct	1152 x 900
	Native	1280 x 1024
Brightness (cd/m <sup>2</sup> )	250	250
Contrast ratio (typ.)	1000 : 1	1000 : 1
Colors	16.7 M	16.7 M
Viewing angle (L/R/U/D)	85/85/80/80	85/85/80/80
Response time (ms)	5	5
Dot pitch (mm)	0.264	0.294
Display area (mm)	337.92H x 270.33V	376.32H x 270.33V
Surface treatment	Haze 25%, Hard-coating	
Surface hardness	3H	
Backlight type	LED	
MTBF (hrs)	30,000	

Mounting Distance	
Display drawer	510 ~ 740 mm 20.1 ~ 29.1 inch

Physical		SP-117	SP-119
Dimensions (W x D x H)	Product	442 x 500 x 44 mm 17.4 x 19.7 x 1.73 inch	442 x 500 x 44 mm 17.4 x 19.7 x 1.73 inch
	Packing	588 x 758 x 120 mm 23.1 x 29.8 x 4.7 inch	588 x 758 x 120 mm 23.1 x 29.8 x 4.7 inch
Weight	Net	10.5 kg / 23.1 lb	12.5 kg / 27.5 lb
	Gross	16.5 kg / 36.3 lb	18.5 kg / 40.7 lb

\* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption	Screen on	Max. 22W
	Power saving mode	Max. 2W
	Power button off	Max. 1W

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

### Diagrams ( mm )

