

AVIP-A4601D-B1C

4K60 HDMI over IP Receiver with USB 2.0



This unit supports both Unicast and Multicast modes, enabling video wall and seamless collaboration across multiple windows in Multicast mode. It supports the transmission of Ultra High-Definition signals (up to 4K@60Hz RGB) with audio and USB 2.0 up to 100m on a single cable which allows connection of USB flash drives, keyboard, and mouse. The transmission distance can be further extended (up to 100m per segment) by using gigabit network switches, allowing the user to cascade the system without signal loss or introducing delay. Moreover, it supports IP to IR and IP to RS-232, converting the IP signal into IR and RS-232 commands for device control.

When the extension system's units are in multicast mode, a single transmitter's AV signal can be sent to a large number of receivers within the same local network without the additional receivers causing the bandwidth requirements to increase. Additionally, that same multicast signal can be used to create large multi-display video walls with amazing simplicity. When combined with the optional IP Master Controller the functionality of the system expands exponentially. Its centralized web-based interface greatly simplifies control and management of large distributed video matrix or video wall systems adding to their flexibility in large home or commercial installations.

This system also features bi-directional IR and RS-232 pass-through, analog line level in/out, and a microphone input (on the receiver), providing the user with a variety of audio options. The USB functionality allows the system to act like a remote USB hub which, when combined with the HDMI input/output feature, provides a comprehensive USB over IP functionality platform. Configuration information is provided via On Screen Display (OSD) and control is by hotkey, WebGUI, IP Master Controller, and Telnet.

The unit is with Dante Ready which can transmit digital audio channels upon activation and is compatible with any standard Dante audio transmitters/receivers that the audio might be routed to. Dante Ready provides a flexible way to enable and expand the connectivity and interoperability of the world's de-facto AV-over-IP solution, even after the initial purchase. Upgrade your system with Dante and connect to over 4,000 products from 500 manufacturers. Dante Ready is built within the widely used Dante Controller application for Dante audio and video subscription management. Transactions are simple and secure, and device upgrades are seamlessly actioned without the need to enter complex license keys of copy license files.

PANELS



FEATURES

- 4K@60 1Gbps AV over IP transmitter in Unicast or Multicast mode.
- IP interface: RJ45
- Supports comprehensive USB over IP functionality (USB flash drive, keyboard and mouse) and seamless collaboration across multiple windows
- Supports PoE-PD (IEEE 802.3af).
- Support IP to IR/ RS-232, converting the IP signal into IR and RS-232 commands for device control.
- Controlled via hotkey, WebGUI, IP Master Controller, and Telnet
- Supports the use of an external control center (IP Master Controller) to provide expanded functionality (Contact your authorized dealer for more information)

- 7 hotkeys dedicated to routing for transmitters and receivers, 4 hotkeys provide single functions, and 3 hotkeys for multiple functions that activates control system
- Supports independent breakaway A/V and control matrix routing
- Supports extension of many audio formats including 8 channel LPCM and standard Bitstream

Note: The Line Out only supports LPCM 2.0 sources.

- The analog Line In is automatically embedded in the streaming output and can be independently routed to any receiver
- The Mic In sends audio directly to the analog Line Out on the currently routed transmitter
- *Note: Only available when the transmitter also has its Line In connected.*
- Optional Dante Ready™ is compatible with existing Dante and AES67 audio networks
- Dante Ready brings Dante functionality to products already shipping and installed in sites
- Channels and features can be added as an installation grows

SPECIFICATIONS

RX

Interfaces

Input Port	1×Mono Audio (3.5mm)
Output Port	1×HDMI (Type-A) 1×Stereo Audio (3.5mm)
Input/Control Port	1×GbE LAN (RJ-45)
Pass-through Port	1×IR Extender (3.5mm) 1×IR Blaster (3.5mm) 1×RS-232 (3-pin Terminal Block) 3×USB 2.0 (Type-A)

Video

HDMI Compliance	HDMI 2.0 (DVI 1.0)
HDCP Compliance	HDCP2.2
Input Signal Type	4096x2160p@60 8bit RGB
Output Signal Type	4096x2160p@60 8bit RGB

Resolutions

Maximum Input	LAN(Streaming)	4096x2160p@60
Maximum Output	HDMI	4096x2160p@60

Audio

Digital Format	HDMI	LPCM (8Channels), Bitstream, High Bit Rate Bitstream
	Line Out	LPCM (2 Channels)
Line Out	Mic In	300 mVrms, S/N Ratio: > 80dB (1kHz with 0dBFS)
	Line Out	2 Vrms, S/N Ratio: > 80dB (1kHz with 0dBFS)

Power

Power Supply	PoE (802.3af) or 12V/3 A
Power Consumption	17.68W

Enclosure

Chassis Material	Metal (Steel)
Chassis Color	Black
Dimensions (W×H×D)	231.5mm×25mm×108mm [Case Only] 231.5mm×25mm×120mm [All Inclusive]
Weight	660g

Field Firmware Update

WebGUI

ORDERING INFORMATION

Model No.	Product Description
AVIP-A4601D-B1C	4K60 HDMI over IP Receiver with USB 2.0
AVIP-A4601E-B1C	4K60 HDMI over IP Transmitter
CDPS-CS11	4K60 over 1G IP Master Control

DIAGRAM

