



IP CAMERA HS-D071SJ-D

- H.265 / H.264
- 5MP (2592 × 1944)
- 20 ~ 30 M IR night view distance
- 3D DNR, DWDR, HLC, BLC, Digital Defog
- ICR auto switch, true day / night
- Built-in micro SD card slot, up to 128GB
- Support ROI coding
- Support three streams
- IP67 ingress protection
- Intelligent analytics: Object removal detection (object left/missing), scene change detection, video blur detection, intrusion detection and line crossing detection

RoHS CE FC





HS-D071SJ-D

Camera			
Image Sensor	1 / 2.7 " CMOS		
Image Resolution	2592 × 1944		
Electronic Shutter	1 s ~ 1 / 100000 s		
Min. Illumination	0.0236 lux @F2.0, AGC ON; 0 lux with IR 0.0085 lux @ F1.2, AGC ON; 0 lux with IR		
FOV	Horizontal	Vertical	Diagonal
Lens 2.8 mm @F2.0	93.4°	77°	106°
FOV	Horizontal	Vertical	Diagonal
Lens 3.6 mm @F2.0	79.4°	63.8°	92°
Lens Mount	M12		
IR Distance	20~30 m		
WDR	Digital WDR		
Day & Night	ICR auto switch		
BLC	YES		
HLC	YES		
Digital Defog	YES		
Digital DNR	3D DNR		
Angle Adjustment	Pan: 0° ~360° ; Tilt:0° ~75° ; Rotation: 0° ~360°		
Image			
Video Compression	H.265 / H.264		
H.264 Compression Standard	Main Profile @Leve4.1 High Tier		
Resolution	5MP (2592 × 1944) , 4MP (2560 × 1440) , 1080P (1920 × 1080) , 720P (1280 × 720) , D1, CIF, 480 × 240		
Main Stream (S1)	60Hz : 5MP@20fps , 4MP / 1080P / 720P @30fps 50Hz : 5MP@20fps , 4MP / 1080P / 720P @25fps		
Sub Stream (S2)	60Hz : 720P @15fps , D1 / CIF @30fps 50Hz : 720P @12fps , D1 / CIF @25fps		
Third Stream (S3)	60Hz : D1 / CIF / 480 × 240 @30fps 50Hz : D1 / CIF / 480 × 240 @25fps		
Bit Rate	64 Kbps ~ 5 Mbps		
Bit Rate Type	VBR / CBR		
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness ,NR,etc. adjustable through client software or web browser		
ROI	Each ROI to be configured separately		
Audio			
Audio Compression	-		
Two-way audio	-		
Interfaces			
Network	RJ45		
Video Output	-		
Audio line in	1CH External MIC ; Built-in MIC × 1		
Audio line out	-		
Alarm Input	-		
Alarm Output	-		
Storage			
SD card	Built-in micro SD card slot; up to 128GB		
Network remote storage	YES		
Hardware Reset	YES		

Functions	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 4 users Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPs, QoS
Interface Protocol	ONVIF
Smart Alarm	Motion detection
Intelligent Analytics	Object removal detection (object left/missing), scene change detection, video blur detection, intrusion detection and line crossing detection
General function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock
PoE	YES
Others	
Power Supply	DC12V / PoE
Power Consumption	<5 W
Operating Environment	- 30 ° C ~ 60 ° C (-22° F~140° F) Humidity: less than 95 % (non-condensing)
Dimensions	Φ 94.6 × 82.8 mm
Weight	Approx. 450g
Installation	Ceiling mounting; Wall mounting
Ingress Protection	IP67

Accessories			
			
B627	B639	B609	
			
B615	B616	B642	B628