

Hybrid DVR HS-HP4311

Product Features

- Time slice instant search
- Fast local back up
- FTP cloud back up
- Private DDNS service
- Push notification
- NVR remote recording
- RTSP streaming
- IP camera recording
- NVMS 2.0 management
- HI SHARP APP
- Support (8MP / 5MP / 4MP / 3MP / 1080P / 720P / WD1 / D1) TVI / AHD / CVI video input
- Support 2CH (8MP / 5MP / 4MP / 3MP / 1080P / 720P / WD1 / D1) IP video input by default
- Support audio over coaxial (TVI mode) *

Specifications



Model		HS-HP4311	Model		HS-HP4311	
Input	AHD/TVI/CVI	4CH	Multi-task	Live / Record / Playback / Network / Backup		
	Max IPC Connection	6CH (4+2) *		Record Quality	Highest / Higher / Medium / Lower / Lowest	
	Total Connection	6CH			Record Mode	Manual / Schedule / Motion / Alarm / Smart event
Output	HDMI	3840 x 2160 / 1920 x 1080 / 1280 x 1024 / 1024 x 768	Audio Line In / Out			4 CH Input * , 1 CH Output
	VGA	1920 x 1080 / 1280 x 1024 / 1024 x 768		Alarm Line In / Out		4 CH Input, 1 CH Output
	CVBS	MAIN / SPOT			External Interface	SATA
Compression Method	H.265 High profile H.264 High profile	E-SATA	E-SATA x 1			
Display Channel	1 / 4 / 6 / 8 / 9	USB	Front panel : USB 2.0 x 1 Rear panel : USB 2.0 x 1			
IPC Maximum Access Level	8MP @20 fps Others @30 fps	Network	RJ45 10 / 100M Base-T x1			
Bit Rate	32 Kbps~ 4 Mbps	Serial	RS485 x 1 (connect to PTZ or keyboard)			
Recording Resolution (HD Analog)	8MP	6 (PAL) / 7 (NTSC) (only CH 1 Support)	PTZ Control	PELCO-P, PELCO-D, CoC (UTC)		
	8MPL	48 (PAL) / 60 (NTSC)	Mobile Surveillance	iOS / Android		
	5MP	48 (PAL) / (NTSC)	Network remote backup	Yes		
	5MPL	80 (PAL) / (NTSC)	Network	Function	Support Licensed CMS / APP / IE	
	4MP / 3MP	48 (PAL) / 60 (NTSC)		Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP	
	4MPL	100 (PAL) / 120 (NTSC)		Client Application	Display / Playback / Backup / DVR control / PTZ control	
	1080P	100 (PAL) / 120 (NTSC)		Web Client	Max 10 users online ▲	
720P / WD1 / D1	100 (PAL) / 120 (NTSC)	Network Access Bandwidth	Input	16 Mbps		
Recording Resolution (IP)	Resolution		8MP / 8MPL / 5MP / 5MPL / 4MP / 4MPL / 3MP / 1080P / 720P / WD1 / D1	Output	40 Mbps	
	Recording Rate	8MP @ 20fps (PAL / NTSC) Others @25 (PAL) / 30 (NTSC) per channel	Power Source	DC12V /2A		
Playback	Simultaneously Local Playback	4CH	Power Consumption	≤ 10W (Without HDD)		
	Search Mode	Date & Time search / Event search	Operating Temperature	5° C ~ 40° C (41° F ~ 104° F) ; 10% ≤ Less than ≤ 90%		
	Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events	Dimension(mm)	300 x 248.5 x 48.1 (W x D x H)		
	Function	Play / pause / FF / FB / digital zoom				

* Support with Firmware V 1.3.8

▲ Max online user simultaneously does not mean full channel view for each user.

Dimension (mm)

