



HS-NK6321



NVR Network Video Recorder

- Plug & Play supported.
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device.
- Mobile remote surveillance. (iOS / Android)
- 2 way audio. (conference)
- Support 16 CH playback. 1 / 4 / 9 / 16 CH
- Network online user management.
- Multi-user online simultaneously.
- Recorded file protection supported.
- Supports multiple browsers.
- Support ONVIF / RTSP connection.
- Support face detection and comparison.
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception.
- Support license plate recognition

RoHS **CE** **FC**



WITH CAMERA



HS-NK6321

System	
Compression	H.265+ / H.265 / H.264
Operating System	Embedded Linux
Video	
Network Input	16 CH
Network Access Bandwidth	160 Mbps
Resolution	12MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 1280 x 1024 / 960P / 720P / 960H / D1 / CIF
Output	HDMI 1 : 3840×2160 / 1920×1080 / 1280×1024 / 1024×768 HDMI 2 : 1920×1080 / 1280×1024 / 1024×768 VGA ×1 : 1920×1080 / 1280×1024 / 1024×768
Audio	
Network Input	16 CH
2-way Audio	RCA × 1
Local Output	RCA × 1
Record	
Record Stream	Dual / Single stream recording
Mode	Manual / timer / motion / sensor / smart events
Frame Rate	12MP: 20fps 8MP or lower resolution: NTSC: 30fps
Playback	
Simultaneous Playback	Max 16 CH
Search	Time slice / time / event / tag search / smart search
Function	Play / pause / FF / FB / digital zoom
Alarm	
Mode	Manual / sensor / motion / exception / smart events
Alarm Input (IPC)	16 CH
Alarm Input (NVR)	8 CH
Alarm Output (IPC)	16 CH
Alarm Output (NVR)	4 CH
Triggering	Record / snap / preset / e-mail
Storage	
SATA	2
e-SATA	-
Capacity	max 14TB per HDD
Backup	
Local Backup	USB disk / USB mobile HDD (limited)
Network Backup	Yes
Mobile Device	
Operating System	iOS / Andriod

Face Detection Function	
Channel	16 CH
Face Picture Database	32 libraries 10000 Face Pictures
Computing Capability	18 pictures / second
Face Picture Search	Search by picture is supported
Database Management	Add, modify, delete and search face pictures
Face Picture Adding	Add face pictures through APP,WEB and external import
Face Picture Comparison	Support allow list, block list and stranger match alarm
Face Trace	Yes
Statistic Graph of Face Information	Bar graph
Statistic Mode of Face Information	Statistics by day, week, month,quarter as well as customized time period
External Interface	
Network Interface	RJ45 1000 Mbps × 2
PoE Port	-
Statistic Mode of Face Information	USB 2.0 × 2 (front panel x 1) (rear panel x 1) USB 3.0 × 1 (rear panel x 1)
Remote Controller	optional
Network	
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPS, 802.1x, RTSP, SNMP, ONVIF
Network-Function	Support licensed CMS(100CH) / Web Client
Web Client	Max. 10 users access
Client Application	Preview / Playback / Backup / PTZ control
Others	
Power Supply	DC12V / 4A
Consumption	≤ 20W (without HDD)
Dimensions	380 × 268 × 48.1 (W × D × H) mm
Operating Temperature	-10 ~ 50 °C
Operating Humidity	10% ~ 90% humidity