




XK-68 Jog & Shuttle Product Manual

- ❑ Part# XK-0990-UBG68-R
- ❑ 68 Keys with Embedded Jog & Shuttle
- ❑ Individual Key Backlighting
- ❑ Designed, Sold, and Supported in USA
- ❑ From P.I Engineering, *The No Slogan Company*
- ❑ USA: www.xkeys.com
- ❑ UK: www.x-keys-uk.com



Box Contents

This package contains:

- 1- X-keys XK-68 Jog & Shuttle
- 1- Replacement key set (2 tall, 1 wide, 1 key puller)
- 2- Angled feet
- 2- Legend Sheets (1 blank, 1 pre-printed)
- 1- Product Manual

Quick Start for Windows

1. Download and install MacroWorks 3.1 (MW3) from:
<http://xkeys.com/PIsupport/SoftwareMacroWorks.php>
2. Plug in the X-keys and wait for Windows to recognize it.
3. Press the programming switch (located on the top edge of the unit) to open the MW3 programming window (or click on the MW3 taskbar icon and select the device).
4. Press any key on the X-keys (or double-click on the key image) to begin recording a macro.
5. Type keystrokes or select text, shortcut, or function. Multiple lines of keystrokes, text, shortcuts, and functions may be entered on a single key.
6. Press the key again (or click Save) to complete programming.
7. When finished, press the programming switch again to close the programming window.

To quickly learn how to use MW3 watch the brief tutorials on our website. Consult the MW3 help file for complete instructions and tips on programming and using your X-keys.

Developers

P.I. Engineering offers a free Software Development Kit with code samples in C#, C++ and .NET. We also offer an SDK for OS X, Linux, and Android application samples. Please visit the Developers section on our website: xkeys.com/PISupport/Developer.php.

Support

Should you encounter difficulty with the installation or programming, please open the MW3 or ControllerMate Help File or post a question in our support forum: xkeys.com/PISupport/Forum.php.

You may also contact technical support.

USA: tech@xkeys.com | Phone: 1-517-655-5523

UK: xkeys@keyboardspecialists.co.uk | Tel +44 (0)20 3474 0234

Compatibility

Unless supported natively by an application (vMix for example), X-keys USB devices require MacroWorks 3 for Windows XP, Vista, or 7-10 or ControllerMate for Mac OS X.

Identifying the Keys

Select appropriate icons or use the blank legend sheet to create your own key legends. The keycaps snap off with a fingernail or small screwdriver. Apply the label under the keycap, and replace it. The key caps hold a legend 0.575" wide and 0.5" high (14.6mm x 12.7mm). Other options are available for printing legends for multiple units. See more information on our website.

Horizontal and Vertical Double-keys

The included double-keys replace two single keys on the X-keys. To install a double key cap, remove two adjacent keys with the provided key-puller. Pressing the key puller over an adjacent key and working it under the cap to be removed is the recommended method. Press the double-key in place over the two exposed switch stems and configure it in MW3 using the Large Key Wizard in the Tools menu. Large quad (2x2) keycaps are also available.

Backlighting

All keys on the X-Keys have two backlighting colors (red and blue) and advanced programming functions in MW3 allow the user to manipulate them. By default when MW3 recognizes the X-keys, blue backlighting indicates the unit is ready for operation or programming. If you program a red layer shift or toggle key, the backlighting will also indicate the active layer.

Feet

The included angled feet may be snapped in to the bottom of the X-Keys to give it a slight tilt in either portrait or landscape orientation.

Compatible Accessories

Please visit the Accessories page on our website for details on the following.

- ☒ X-keys USB Extender – up to 150 feet via CAT 5 cable
- ☒ Tall, wide, and quad keycaps
- ☒ Colored and transparent key caps
- ☒ Blank key blockers

Other Products from P.I. Engineering

- ☒ X-keys XK-24 – 24 programmable keys
- ☒ X-keys XK-12 Joystick – 12 keys with a precision joystick
- ☒ X-keys XK-12 Jog & Shuttle – 12 keys with jog & shuttle
- ☒ X-keys XK-3 Foot Pedal – three programmable pedals
- ☒ X-keys XK-4 Stick – four programmable keys
- ☒ X-keys XK-8 Stick – eight programmable keys
- ☒ X-keys XK-16 Stick – sixteen programmable keys
- ☒ X-keys XK-68 Joystick - 68 keys with a precision joystick
- ☒ X-keys USB 12 Switch Interface – 12 switch ports
- ☒ X-keys USB 3 Switch Interface – 3 switch ports
- ☒ X-keys Matrix Board – 128 switch points

FCC Declaration of Conformity

This device complies with Part 15 of the FCC rules.

Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and if not installed and used in accordance with the instruction manual may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio TV technician for help.

Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

CE Declaration of Conformity

We, P.I. Engineering, Inc., declare that the X-keys is in conformance with:

- EMC Directive 2014/30/EU, tested in accordance with EN 55032:2012 and 55024:2010/A1:2015
- Certificate of compliance on file at P.I. Engineering, 101 Innovation Pkwy, Williamston, MI 48895



Contact Us

<p align="center">USA Sales</p> <p>sales@piengineering.com Phone: 1-517-655-5523 www.xkeys.com</p>	<p align="center">USA Technical Support</p> <p>tech@piengineering.com Phone: 1- 517-655-5523 www.xkeys.com/support.php</p>	<p align="center">USA Shipping Address</p> <p>P.I. Engineering 101 Innovation Parkway Williamston, MI 48895-1663</p>
<p align="center">UK Sales</p> <p>xkeys@keyboardspecialists.co.uk Tel +44(0)20 3474 0234 www.x-keys-uk.com</p>	<p align="center">UK Technical Support</p> <p>www.x-keys-uk.com xkeys@keyboardspecialists.co.uk Tel +44(0)20 3474 0234</p>	<p align="center">UK Shipping Address</p> <p>Keyboard Specialists Ltd Unit 44-45, Salisbury Street Darlaston West Midlands WS10 8XB United Kingdom</p>

Limited Warranty

For all X-keys products purchased and installed in the United States and Canada, P.I. Engineering warrants that the X-keys product will be free from defects in materials and workmanship under normal use and service, and will meet the specifications presented by P.I. Engineering at the time of original purchase, for one year as evidenced by a copy of the purchase receipt. Under this warranty, P.I. Engineering will, at its sole option, repair or replace any X-keys product which is defective, provided that you are responsible for (i) the cost of transportation of the product to P.I. Engineering or its designated service facility, and (ii) any loss or damage to the product resulting from such transportation.

Upon discovery of a defect in the product within the Warranty Period, you should notify P.I. Engineering Technical Support via telephone to obtain an RMA (return authorization number) and instructions for shipping the product to a service location designated by P.I. Engineering. You should send the product, shipping charges prepaid, to the designated location, accompanied by the return authorization number, your name, address, and telephone number, proof of purchase, and a description of the defect. P.I. Engineering will pay for return of product(s) to the customer.

P.I. Engineering shall have no responsibility to repair or replace the X-keys product if the failure has resulted from accident, abuse, mutilation, misuse, or repair/modification performed by any entity other than P.I. Engineering.

THIS WARRANTY IS EXCLUSIVE OF ALL OTHER WARRANTIES, WHETHER EXPRESSED, IMPLIED, OR STATUTORY. P.I. ENGINEERING DOES NOT WARRANT THIS X-keys PRODUCT FOR FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. P.I. ENGINEERING AND ITS EMPLOYEES SHALL NOT BE HELD LIABLE FOR ANY CONSEQUENTIAL, INDIRECT, OR INCIDENTAL DAMAGES, EVEN IF ADVISED OF THEIR POSSIBILITY, ARISING OUT OF THE USE OR INABILITY TO USE THIS PRODUCT. SOME STATES DO NOT ALLOW FOR THE EXCLUSION OR LIMITATION OF CERTAIN LIABILITIES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER LEGAL RIGHTS WHICH VARY FROM STATE TO STATE.

In the event that the above limitations are held unenforceable, P.I. Engineering's liability for any damages to you or to any party shall not exceed the purchase price you paid, regardless of the form of any claim.

This limited warranty is valid for and only applies to products purchased and used inside the United States (and its territories) and Canada.

This limited warranty is governed by the laws of the United States of America and the state of Michigan.

X-keys Electronic design: P.I. Engineering, Inc., Williamston, Michigan
 Patent # 4964075

© 2019 P.I. Engineering, Inc. All rights reserved.

Y-mouse, Y-see two, Y-key key, X-keys, and the "P.I. Eclipse" are trademarks of P.I. Engineering, Inc.
 PS/2 is a registered trademark of International Business Machines, Inc.
 All other trademarks are property of their respective owners.

USA: www.pieengineering.com ■ www.xkeys.com

UK: www.x-keys-uk.com

PI Part#1205

