

8K DP  
USB-C

# CAHBP-P3122-13



**2 Ports Dual Monitor Hybrid KVM Switch ( DP 1.4 + USB-C )  
with USB 3.2 Gen 1, USB Audio, PD Charging, Hotkey Control**

## Specifications

<b>Model Number</b>	<b>CAHBP-P3122-13</b>	
<b>MAX. Resolution</b>	4K@60Hz ( 4:4:4 ) ( Main, USB-C ) 8K@60Hz ( 4:4:4 ) ( AUX, DP 1.4 )	
<b>Interfaces</b>	<b>PC Side</b>	<b>Console Side</b>
<b>Video Switching ( AUX<sup>1</sup> )</b>	DP 1.4 x 2 ( In )	DP 1.4 x 1 ( Out )
<b>Video Switching ( Main )</b>		4K DP x 1
<b>USB 3.2 Switching</b>	USB-C x 2 ( DP Alternate Mode )	<b>Rear USB :</b> USB HID x 3 ( A ) USB 3.2 x 1 ( A )
<b>USB Audio Switching</b>		<b>Front USB :</b> USB HID x 1 ( A ) USB 3.2 x 1 ( A ) SPK x 1 ( Out ) MIC x 1 ( In )
<b>USB-C Bandwidth Allocation*</b> ( Apply 4-Lane + U2 in Most Cases )	4-Lane + USB 2.0 2-Lane + USB 3.2	
<b>MAX. USB-C PD</b>	PC1 : 20V@3A PC2 : 20V@3A	
<b>Control Methods</b>	Push Button / Hotkey ( USB HID )	
<b>HDCP Compliance</b>	HDCP 2.2 & HDCP 1.4	
<b>Hot Plug-and-Play</b>	Yes	
<b>Push Buttons</b>	PC Select x 1	
<b>Slide Switches</b>	USB-C Bandwidth x 1	
<b>LED Indicators</b>	PC-Ready x 2, PC-Select x 2	
<b>Power supply</b>	DC 19~21V	
<b>Operation Environment</b>	0~40°C, Humidity<80% ( Storage : -20~60°C )	
<b>H x W x D ( mm )</b>	64 x 160 x 100	
<b>Weight ( g )</b>	780	
<b>Material</b>	Metal	


\* High Quality Cables Are Required to Run High-Resolution Video

\*\* The USB-C Video Is Based on DP Alternate Mode. USB 4 / TB 4 Sources' Compatibility with USB-C & Mobile Devices' Compatibility with KB/MS Should Be Checked In the Sources' Manuals.

## Features

- Allows 2 PCs Share 1 Set of KVM Console
- **USB-C Video ( Main )** Supports Most Popular Resolutions Up to 4K@60Hz ( 4:4:4 )
- **DP 1.4 Video ( AUX )** Supports Most Popular Resolutions Up to 8K@60Hz ( 4:4:4 ) ( Along with VRR / DSC / High-FPS Gaming Applications )
- **20V USB-C PD** Allows User to Flexibly Deliver USB-C Power and Keeps the Laptop Plugged-in, Also Supports USB 5V Charging Up to 3A
- **USB-C Bandwidth Allocation** Allows Wider Compatibility Including Two Types :
  - 4-Lane + USB 2.0 ( Apply in Most Cases )
  - 2-Lane + USB 3.2 Gen 1
- **USB Audio** Simplifies Physical Connections with Unique USB Audio Allocations :
  - 0 : Disable USB Audio
  - 1 : USB MIC Only
  - 2 : USB SPK & MIC
  - 3 : USB SPK Only
- **HDCP 2.2 and HDCP 1.4 Compliance**
- **HDR10** Support for Best Visual Experience ( DP 1.4 Videos Only )
- **USB 3.2 Gen 1** Provides Excellent 5 Gbps Speed
- **Front USB** Allows Easy Access

### Front USB



### USB Audio

### USB-C PD

## Connection pattern



## Order Information

Model	Video	USB-C PD
CAHBP-P3132-13	Triple-Monitor ( 4K USB-C + DP 1.4 x 2 )	MAX. 120W ( Total )
CAHBP-P3122-13	Dual-Monitor ( 4K USB-C + DP 1.4 x 1 )	
CAAB-P3112-13	Single-Monitor ( 4K USB-C )	

\*Certain Models Available Upon Bulk Orders